



ValueJet 1638UR MarkII

UV LED Printer — Roll-to-Roll —

Compatible with 1625mm/64" wide roll media

MUTOH's intelligent interweave print technology "I-WeaveUVEX" delivers high density/contrast image quality while maintaining faster production speeds

BEAUTIFUL PRINTS, FASTER

Versatile applications
Diverse Expressiveness
Higher production capacity

Developed for the commercial print and sign & display markets

Expanding the range of options with 6 colour (CMYK + white and varnish)


UV light allows exceptional cure times and instant drying







High quality graphics and high productivity



The staggered dual print heads with dual UV lamps on both sides provide higher productivity which achieves the print speeds up to 22.7m2/h. The UV lamp

control setting function enables the expression of delicate image for professional use.

Lineup of take-up units support up to 30kg, 40kg and 100kg.



Take-up unit up to 40kg

MUTOH UV LED ink - Flexible type

It is ideal for flexible applications using roll media. White and varnish inks enable printing on transparent media and colored materials, reducing unevenness, as well as special effect printing. MUTOH's UV ink is VOC-free, and has low odor after curing. As it's cured at low temperature, it can be used on heat-sensitive media. MUTOH's UV ink is U.S. GREENGUARD Gold certified to meet the U.S. environmental standards.

Multi-layer printing capability

Multi-layer printing using CMYK, white, and varnish achieves rich and various expressiveness, and brings out the potential of various applications.

*Layer printing requires a RIP software that supports layer printing. With the layer editor, colour, white, and varnish data created by the RIP can be received individually, set up to four layers in order, and sent and created at once.

User-friendly features

The VJ-1638UR Mark II improves maintenance operations and provides users easy replaceable cleaning wiper, mist filters, etc. Built-in automatic media cutter increases work efficiency.





Easy access maintenance area Built-in automatic media cutter

MUTOH Genuine RIP Software (included)



- High quality technology to optimize the performance of MUTOH printers
- Two preview functions can reduce mistakes and waste
- Workflow efficency

The newly developed MUTOH intelligent interweave print technology "i-WeaveUVEx" run by MUTOH's genuine RIP software "VerteLith" reduces graininess and banding during high density printing.

Highdensity/contrast image quality while maintaining faster production speeds



V ลีโบยปet.		VJ-1638UR MarkII	
Printing system		Drop-on-demand Micro Piezo Inkjet Technology	
Print head height		Low: 1.5mm High: 2.5mm (3 step system by manual)	
Print head		2 (staggered set-up)	
Media width		Max. 1,625mm / Min. 182mm (Roll media)	
Media measurements		Ø 150mm / 2" & 3" / 30kg or less	
Maximum media thickness		0.3mm for head height "low" setting 1.3mm for head height "high" setting	
Maximum printable width		1,615mm	
UV lamp		UV LED 2 pcs	
	Туре	UV LED ink (flexible type)	
Ink	Ink set	4 colors(C, M, Y, K)/ 5 colors (CMYK + Cl + Va) / 6 colors (C, M, Y, K, White + Varnish)	
	Volume	220ml (C, M, Y, K, White + Varnish), 500ml (White), 800ml (C, M, Y, K, Varnish) *	
	No. of slot	8	
Maximum print resolution		1440x1440dpi (16 pass)	
Interface		Gigabit-Ethernet (1000BASE-T)	
Power requirements		AC100-120V/AC200-240V±10%, 50/60Hz±1Hz	
Printable environment		Temperature:20-32°C < Recommended environment: 22-30°C>	
		Humidity: 40-60%RH (non condensing)	
Electrical power consumption		<main> Operation status: 770W or less Standby: 55W or less</main>	
Dimensions (WxDxH)		Printer including stand: 2,983x818x1,261mm	
Weight		Body: 152kg Stand: 37kg	

^{* 500/800}ml bags require optional adapter.



Do not expose your eyes and skins to the ultraviolet while printing. The UV ink (before curing) has strong skin sensitizing property. Always wear the protective plastic gloves during maintenance or disposal to avoid the skin contact with the UV ink. The UV ink is also harmful to water creatures. Do not dump this product into sewers or any body of water, and delegate disposal to an industrial waste disposal contractor.

Optional Items

Product model	Details	
VJ16/19-TUP30	Take-up unit (Supports up to 30kg media)	
VJ16/19-TUP40U	Take-up unit (Supports up to 40kg media)	
VJ-19TUP100U	Take-up unit (Supports up to 100kg media)	
VJ-HCIPADPT-UV8	High capacity ink pack adapter	

■Supplied products

Product name	Product model	Details		
	US11-BK220	Black		
	US11-CY220	Cyan		
	US11-MA220	Magenta	220ml	
	US11-YE220	Yellow		
	US11-VA220	Varnish		
UV LED INK	US11-WH220	White		
(Flexible type)	US11-BK800	Black		
	US11-CY800	Cyan		
	US11-MA800	Magenta	800ml	
	US11-YE800	Yellow		
	US11-VA800	Varnish		
	US11-WH500	White	500ml	
	UH21-CL220	Cleaning fluid	220ml	
	VJ-ULVA1-ML500	Maintenance cleaner		
Other optional	VJ-1638UH-WIP	Wiper Set (2sets/box)		
products	RH 2 clean stick	Clean stick (100pcs/box)		
	PJ-P0LYNITW2	Polyester knit wipers (300pcs/box)		
	VJ-FBPAD-U3	Flushing Absorber (3pcs/b	Flushing Absorber (3pcs/box)	

^{*} The ink and cleaning fluid are required to purchase separately. Once the white ink configuration is set to the printer, it cannot be changed.

MUTOH

Mutoh Australia Pty Ltd Unit 19 / 76 Reserve Road, Artarmon NSW 2064 ph: 02 9437 1366 e: sales@mutoh-au.com web: www.mutoh-au.com Distributed by:

to the printer, it cannot be changed.

Prepare total 8 cartridges for 4 colours of CMYK x 2 each, 5 colors of CMYK each + Varnish x 2 + CL x 2, or 6 colours of CMYK each + White x 2 + Varnish x 2.

^{*} Ink adhesion will vary among media type and brand. Individual testing is required in function of your specific application.

^{*} As the white ink will precipitate, please handle it according to the "Precautions for using special ink" included in the package before daily use.